

## NL-26 Drill Specifications

<b>Drilling Capacity</b>	150 – 200M
<b>Swivel Head</b> Type Spindle I.D. Spindle Stroke Angle Range Spindle RPM Chuck	Hydraulic Twin Cylinders 47 mm 500 mm 360° 72, 110, 144, 220, 292, 448 Hydraulic Chuck
<b>Gearing</b> Type Clutch Input RPM	Sliding Gear Single Disc type 1,200 rpm
<b>Hoist</b> Type Drum Size Dia. of Rope Drum Capacity Hoisting Speed Hoisting Capacity Cone Pulley	Planetary Gear 120 mm Dia. x 125 Length 9 mm diameter 30 meters 14, 25, 48m/min. 1,000 kgs. Standard Accessories
<b>Hydraulic Pump</b> Type Output Volume Running Pressure Max. Pressure	Vane Type, Variable Out-Put 0 – 20 L/min. 0 – 50 kgf/cm <sup>2</sup> 70 kgf/cm <sup>2</sup>
<b>Frame</b> Frame Type	Skid Type
<b>Power Unit</b> Electric Motor Engine	5.5KW – 4P 8 PS
<b>Safety Cover</b> Swivel Head Guard Cone Pulley Guard	
<b>Weight</b> Less Power Max. Disassembled weight	450 kgs. 60 kgs. (without Power)
<b>Option</b> Manual Chuck Assy Hydraulically Slide Base	